

**iQ parts**  
IQ-PARTS-SHOP.COM



**SPECS &  
INFORMATION**

## Product description

### Light weight and very flexible exhaust gas ducting of TPE-coated polyester fabric

**Material:**

TPE-coated polyester fabric, black

Helix: PA 6.6, heat-stabilized Wear Strip Profile: TPE, black (coloured profile available upon request)

**Temperature Resistance:**

– 40° up to + 150° C (intermittent + 170° C)

**Single Length:**

Up from 2,5 to 20 m available

**Applications:**

Suction of exhaust gases in over-floor applications with reel systems or suction channels

**Properties:**

Excellent chemical resistance, especially against oil and petrol fumes, crush recoverable

Stand: 01.09.2020

Technical data				
Dia. (mm)	Weight (kg/m)	Wall Thickness (mm)	Bending radius (mm)	Max. Vacuum (bar)
40	0,25	0,4	80	0,65
50	0,41	0,4	85	0,50
65	0,53	0,4	100	0,35
70	0,61	0,4	105	0,20
75	0,69	0,4	105	0,15
80	0,74	0,4	160	0,12
90	0,83	0,4	175	0,12
100	0,87	0,4	190	0,10
125	1,20	0,4	250	0,08
150	1,44	0,4	300	0,06
200	1,83	0,4	400	0,04
250	2,29	0,4	500	0,02





info@iq-parts.nl  
Harsweg 34A  
2461 EZ Ter Aar  
T +31 252 624 126  
The Netherlands