

iQparts
IQ-PARTS-SHOP.COM



**SPECS &
INFORMATION**



Suction and delivery hose in pvc with food grade quality and steel spiral, suitable for the transport of a multitude of media.

Temperature: -10°C to +60°C

Construction: transparent pvc with food grade quality and a a steel spiral embedded in the hose wall, smooth in- and outside

Passage of food products or liquids according to simulants A, B, C, and D1 (approved by the IANESCO testing laboratory E19-10417)

Remarks:

- Toleranties: ± 1 mm

Applications

public work, agriculture, pumps, ...

Reference	Diameter (mm)	Wall thickness (mm)	Weight (g/m)	Bending radius (mm)	Working Pressure (bar)	Vacuum (mH20)	Coil length (m)
PL008	8	3	130	30	5	9	60
PL010	10	3	160	30	5	9	60
PL012	12	3	185	40	5	9	30 - 60
PL014	14	3	210	50	5	9	30 - 60
PL016	16	3,5	250	60	5	9	30 - 60
PL018	18	3,5	290	65	4,5	9	30 - 60
PL020	20	3,5	340	70	4,5	9	30 - 60
PL022	22	3,5	380	75	4	9	60
PL025	25	4	450	75	4	9	30 - 60
PL030	30	4	540	80	4	9	30 - 60
PL032	32	4,5	610	90	4	9	30 - 60
PL035	35	4,5	710	100	3,5	9	30 - 60
PL038	38	4,5	790	110	3,5	9	30
PL040	40	5	860	110	3,5	9	30
PL045	45	5,5	1000	120	3,5	9	30
PL050	50	5,5	1200	130	3,5	9	30
PL060	60	7,5	2000	180	3	9	30
PL063	63	7,5	2100	290	3	9	30
PL070	70	8	2300	360	3	9	30
PL075	75	8	2650	380	2,5	9	30
PL080	80	8,5	2900	410	2	9	20 - 30
PL090	90	8,5	3400	430	2	9	20
PL100	102	8,5	4000	500	2	9	20 - 30
PL105	105	9	4200	520	2	9	20
PL110	110	9,5	4750	560	1,5	9	20
PL120	120	9,5	5250	600	1,5	9	20
PL125	125	9,5	5400	600	1,5	9	20
PL150	150	10	6900	760	1,5	9	20



info@iq-parts.nl
Harsweg 34A
2461 EZ Ter Aar
T +31 252 624 126
The Netherlands