

**iQparts**  
IQ-PARTS-SHOP.COM



**SPECS &  
INFORMATION**

# CLAMP 212



## Bridge clamp for attaching externally corrugated spiral hoses

### Properties

- practically leak-proof and secure clamping with special bridge geometry
- easily and quickly fitted

- re-usable

- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

### Design

- Quality: W2; Clamp strip: stainless steel 1.4301 = AISI 304; Screw: galvanised steel; Body: stainless steel 1.4016 = AISI 430; Bridge: stainless steel 1.4301 = AISI 304 (INOX)
- in accordance with DIN 3017

### Delivery variants

- further diameters available on request

| Suitable for<br>Hose I.D.                                                   | Clamping<br>Range | Band<br>Width | Order No.     |
|-----------------------------------------------------------------------------|-------------------|---------------|---------------|
| (mm)                                                                        | (mm)              | (mm)          |               |
| <b>AIRDUC® &amp; PROTAPE® 44 mm</b>                                         |                   |               |               |
| 13-16                                                                       | 9-19              | 5             | 212-0009-0000 |
| 15-18                                                                       | 13-20             | 5             | 212-0013-0000 |
| 18-26                                                                       | 17-27             | 5             | 212-0017-0000 |
| 22-28                                                                       | 20-28             | 5             | 212-0020-0000 |
| 25-29                                                                       | 22-37             | 9             | 212-0022-0000 |
| 30-35                                                                       | 27-47             | 9             | 212-0027-0000 |
| 32-37                                                                       | 29-47             | 9             | 212-0029-0000 |
| 38-44                                                                       | 35-55             | 9             | 212-0035-0000 |
| <b>CP Ø 38-65 mm, PROTAPE® TPE 326 MEMORY Ø 51-65mm</b>                     |                   |               |               |
| 38-45                                                                       | 35-55             | 9             | 212-0035-2002 |
| 50-55                                                                       | 45-65             | 9             | 212-0045-2002 |
| 60-65                                                                       | 55-75             | 9             | 212-0055-2002 |
| <b>AIRDUC® &amp; PROTAPE® 45 mm, CP &amp; PROTAPE® TPE 326 MEMORY 70 mm</b> |                   |               |               |
| 45-50                                                                       | 40-60             | 9             | 212-0040-0000 |
| 50-55                                                                       | 45-65             | 9             | 212-0045-0000 |
| 60-65                                                                       | 55-75             | 9             | 212-0055-0000 |
| 70-75                                                                       | 65-85             | 9             | 212-0065-0000 |
| 80-85                                                                       | 75-95             | 9             | 212-0075-0000 |
| 90-95                                                                       | 85-105            | 9             | 212-0085-0000 |
| 100-105                                                                     | 95-115            | 9             | 212-0095-0000 |
| 110-115                                                                     | 105-125           | 9             | 212-0105-0000 |
| 120-125                                                                     | 115-135           | 9             | 212-0115-0000 |
| 130-135                                                                     | 125-145           | 9             | 212-0125-0000 |
| 140-145                                                                     | 135-155           | 9             | 212-0135-0000 |
| 150-155                                                                     | 145-165           | 9             | 212-0145-0000 |
| 160-165                                                                     | 155-175           | 9             | 212-0155-0000 |

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data.

## CLAMP 212

| Suitable for<br>Hose I.D. | Clamping<br>Range | Band<br>Width | Order No.     |
|---------------------------|-------------------|---------------|---------------|
| (mm)                      | (mm)              | (mm)          |               |
| 170-175                   | 165-185           | 9             | 212-0165-0000 |
| 180-185                   | 175-195           | 9             | 212-0175-0000 |
| 190-195                   | 185-205           | 9             | 212-0185-0000 |
| 200-205                   | 195-215           | 9             | 212-0195-0000 |
| 210-215                   | 205-225           | 12            | 212-0205-0000 |
| 220-225                   | 215-235           | 12            | 212-0215-0000 |
| 250-255                   | 245-265           | 12            | 212-0245-0000 |
| 260-265                   | 255-275           | 12            | 212-0255-0000 |
| 270-275                   | 265-285           | 12            | 212-0265-0000 |
| 280-285                   | 275-295           | 12            | 212-0275-0000 |
| 300-305                   | 295-315           | 12            | 212-0295-0000 |
| 310-315                   | 305-325           | 12            | 212-0305-0000 |
| 320-325                   | 315-335           | 12            | 212-0315-0000 |
| 350-355                   | 345-365           | 12            | 212-0345-0000 |
| 370-375                   | 365-385           | 12            | 212-0365-0000 |
| 400-405                   | 395-415           | 12            | 212-0395-0000 |
| 450-455                   | 445-465           | 12            | 212-0445-0000 |
| 500-505                   | 495-515           | 12            | 212-0495-0000 |
| 510-535                   | 505-545           | 12            | 212-0505-0000 |
| 550-575                   | 545-585           | 12            | 212-0545-0000 |
| 630-655                   | 625-665           | 12            | 212-0625-0000 |

## Accessories



CONNECT 228



CONNECT 270-271





**iq**  
**parts**  
IQ-PARTS-SHOP.COM

info@iq-parts.nl  
Harsweg 34A  
2461 EZ Ter Aar  
T +31 252 624 126  
The Netherlands